



# America's Choice<sup>®</sup>



## Typical Properties NGP Natural Gas Diesel Motor Oils

**America's Choice** NGP ENGINE OIL 15W-40 IS A PREMIUM QUALITY OIL DESIGNED TO SATISFY THE REQUIREMENTS OF NATURAL GAS AND PROPANE FUELED HEAVY DUTY ENGINES. ITS LOW ASH AND PHOSPHOROUS CONTENT MAKES IT COMPATIBLE WITH CATALYTIC CONVERTER EQUIPPED ENGINES. NGP EXCEEDS API QUALITY LEVEL CD, AND MEETS ENGINE MANUFACTURERS'

SPECIFICATIONS FOR USE IN THEIR NATURAL GAS ENGINES, AS FOLLOWS:

	America's Choice NGP	America's Choice NGP-2
CUMMINS L10G	ö	
CUMMINS B5.9G, C8.3G		ö
DETROIT DIESEL SERIES 50G	ö	

### TYPICAL PROPERTIES

	NGP	NGP-2
SAE Viscosity Grade	15W-40	15W-40
Density, kg/m <sup>3</sup> @ 15°C.	876	876
Viscosity, kinematic (D445):		
Cst @ 100°C.	15.5	15.5
cSt @ 40°C	135	135
Viscosity Index	120	120
CCS Viscosity (D5293), cP @ -15°C.	3200	3200
Flash Point, °C.	240	240
Pour Point, °C.	-33	-33
TBN (D2896)	5.3	5.3
TAN (D664)	0.6	0.6
Sulphated Ash, %wt.	0.3	0.3
Phosphorous Content, ppm	300	725
Zinc Content, ppm	310	750
Calcium Content, ppm	1200	1200

Note: The values shown are representative of current production and may vary within modest ranges.

FORM 2203

CREATED 07/28/99