

America's Choice



Typical Properties Universal Tractor Fluid

America's Choice UNIVERSAL TRACTOR FLUID IS A HIGH QUALITY TRANSMISSION/ DIFFERENTIAL/ HYDRAULIC FLUID RECOMMENDED FOR USE IN POWERSHIFT/HYDROSTATIC/MANUAL TRANSMISSIONS, DIFFERENTIALS, FINAL DRIVES, WET BRAKES/CLUTCHES, POWER STEERING AND PTO DRIVES COMMONLY USED IN FARM AND CONSTRUCTION EQUIPMENT, OFF-HIGHWAY VEHICLES AND INDUSTRIAL TRACTORS.

FEATURES

- Minimizes wet brake and clutch chatter for vibration free operation.
- Compatible with seal materials used for the applications recommended.
- Excellent EP properties to reduce gear pitting and wear.
- Excellent antiwear properties for longer bearing and hydraulic pump life.
- Provides a wide temperature operating range for summer and all but the most severe winter operations. Viscosity range equivalent to a 5W20 engine oil.
- Good corrosion protection even in the presence of moisture.
- Long fluid life due to its excellent oxidative stability.
- Good filterability.

APPLICATIONS:

- John Deere J20A, J20C.
- Ford New Holland M2C41B, M2C48B, M2C48C, M2C86C, M2C134D.
- Massey-Ferguson M1110, M1127A, M1127B, M1129A, M1135, M1139, M1141.
- J.I. Case MS1204 (J1C185), MS105, MS1206, MS1207, MS 1210 (J1C145).
- Kubota B6 (UDT).
- IHC B-6
- Deutz-Allis (PF821XL), Versatile (23M or 24M), Landini, Fiat-Hesson.
- Power shift transmissions specifying Allison C-3/C-4 or CAT TO-2 fluids.
- Mobile equipment hydraulic systems.
- Vickers 35VQ25.
- White Farm Q1826.

TYPICAL PROPERTIES

SP. Gravity @ 15.6 °C		0.880
Viscosity	cSt @ 40 °C	64.0
	cSt @ 100 °C	9.4
Viscosity Index		130
Pour Point, °C		-39
Flash Point, °C		210
Color, (ASTM)		3.0

Note: The values shown are representative of current production and may vary within modest ranges.